


DIFFERENTIAL PRESSURE TRANSMITTER PRE-28

- ✓ Overloads up to 413 bar total static pressure
- ✓ Accuracy 0,25%
- ✓ Any range from 0...16 mbar up to 0...25 bar
- ✓ Intrinsic safety certificate (ATEX, IECEx)
- ✓ Marine certificate – DNV, BV



Application

The PRE-28 transmitter is applicable to the measurement of differential pressure of gases, vapours and liquids.

Construction

The active element is a piezoresistance silicon sensor separated from the medium by separating diaphragm and a specially selected type of manometric fluid. The special design of the active sensing element ensures withstanding the pressure surges and overloads of up to 413 bar. The electronics is placed in a casing with a degree of protection IP65, IP67, depending on the type of electrical connection applied.

Calibration

Potentiometers can be used to shift the zero position and the range by up to 10%, without altering the settings.

Installation

The transmitter with P type process connection is not heavy, so it can be installed directly onto impulse lines. For fitting in any desired position on a Ø25 pipe the Aplisens mounting bracket (F125 mounting bracket, page IV/ 5) is recommended.

The version with C type process connection can be fitted directly to a 3- or 5-valve manifold. The factory-mounted transmitters with VM type valve manifold (page IV/ 2) are recommended. A transmitter without a valve manifold can be fitted in any position on a 2\" pipe or on a wall using the C-2\" mounting bracket (page IV/ 5).

When the special process connections are required for the measurement of levels and pressures (e.g. at food and chemical industries), the transmitter is provided with an Aplisens diaphragm seal. The differential pressure transmitters with diaphragm seals are described in detail in the further part of the catalogue.

Technical data

Materials: Wetted parts: type P process conn. SS316L
type P(H) process conn. SS316L or Hastelloy C276
type C process conn. SS316L
Diaphragm SS316L, Hastelloy C276, Au
Casing SS304
Option: SS316

Hysteresis, repeatability 0,05%
Thermal compensation range: 0+70°C
Operating temperature range: -25+80°C
Medium temperature range: -25+120°C (direct measurement)
Over 120°C – measurement with use an impulse line or diaphragm seals

CAUTION: the medium must not be allowed to freeze in the impulse line or close to the process connection of the transmitter.

Technical data

Any measuring range 0...16 mbar ± 0...25 bar

	Measuring Range				
	25 mbar	100 mbar	1 bar	2 bar	25 bar
Overpressure Limit Static Pressure Limit (repeated, without hysteresis)	250 bar (option 413 bar) (40 bar for P type process connection)				
Accuracy	0,4%	0,4%	0,25%		
Long term stability	0,6% / year	0,2% / year	0,1% / year		
Thermal error	Typically 0,6% / 10°C max 1% / 10°C	Typically 0,3% / 10°C max 0,4% / 10°C	Typically 0,2% / 10°C max 0,3% / 10°C		
Zero shift error for static pressure*	0,1% / 10 bar				

* Zeroing the transmitter in conditions of static pressure can eliminate this error.

Output signal 4...20 mA, two wire transmission
0...10 V, three wire transmission

Load resistance
(for current output)

$$R[\Omega] \leq \frac{U_{\text{supl}}[\text{V}] - 85\text{V}}{0,02\text{A}}$$

Load resistance
(for supply output)

$R \geq 20\text{k}\Omega$

Power supply

output 4...20 mA: 8...36 VDC (Ex 9...28 VDC)
version TR: 10,5...36 VDC (Ex 12...28 VDC)

output 0...10 V: 13...30 VDC

Error due to supply voltage changes 0,005% (FSO) / V

Ordering procedure

Model	Code	Description
PRE-28		Differential pressure transmitter
Versions, certificates	/Exia.....	II 1/2G Ex ia IIC T4/T5/T6 Ga/Gb II 1D Ex ia IIIC T110°C Da I M1 Ex ia I Ma
	/Exia (IECEx).....	IECEx II 1/2G Ex ia IIC T4/T5/T6 Ga/Gb Ex ia IIC T4/T5/T6 Ga/Gb
	/MR.....	For ALW, ALM version: II 1/2G Ex ia IIC T4 Ga/Gb II 1D Ex ia IIIC T110°C Da Ex ia IIC T4 Ga/Gb Ex ia IIIC T110°C Da
	/Tlen.....	IECEx
more than one option is available	/TR.....	Marine certificate – DNV, BV (not available in ALW and ALM version) For oxygen service (sensor filled with Fluorolube fluid) Response time <30ms; only 4...20mA output
Measuring range	/...+... [required units]	Measuring range in relation to 4mA and 20mA (or 0 and 10V) output.
Analogue output signal	(without marking) /0+10V.....	4...20mA / power supply 10,5...36VDC (Ex 12...28VDC) 0...10VDC / power supply 13...30VDC
Measuring set range	/...+... [required units]	Calibrated range in relation to 4mA and 20mA (or 0V and 10V) output
Casing, electrical connection	/PD.....	Housing IP65 with DIN EN 175301-803 connector
	/PZ.....	304SS housing, IP66, packing gland M20x1,5
	/PZ316.....	316SS housing, IP66, packing gland M20x1,5
	/PM12.....	304SS housing, IP67 with thread M12x1 and connector with cable (3 m in standard)
	/PK12.....	304SS housing, IP67, cable electrical connection (3 m of cable in standard)
	/ALW *.....	Aluminum housing, local display, IP65, DIN43650 connector
Process connections	/ALM *.....	Aluminum housing, local display, IP65, DIN43650 connector
	/C.....	Thread 1/4NPT F on the cover flanges cover flanges material SS316. Allows mounting with a valve manifold. Process connection of cover flange: M10 (option /C(7/16) - 7/16"UNF acc. to IEC 61518)
	/CR.....	C-type process connection rotated 90°
	/P.....	Thread M20x1,5 (male)
	/PN.....	Thread 1/4"NPT (female)
Material of diaphragms (refers only to C, CR, P, PN process connection)	/code of diaphragm seal....	Diaphragm seal (see chapter of diaphragm seals) mounted on Hi side of transmitter, Lo side 1/4NPT Female
	(without marking).....	Diaphragms material SS316L
	/H.....	Diaphragms material Hastelloy C276
Gasket (refers only to C, CR process connection)	(without marking).....	(all wetted parts in Hastelloy C276 on request)
	/NBR.....	Gold plated diaphragms
	/PTFE.....	FPM Viton
	/C-2".....	NBR
	/C-2"(SS).....	PTFE
	/C-2"B.....	Mounting bracket for 2" pipe (to C process conn.), mat. zined steel
	/C-2"B(SS).....	Mounting bracket for 2" pipe (to C process conn.), mat. Stainless Steel
	/FI25.....	Mounting bracket for 2" pipe (to C(7/16) process conn.), mat. zined steel
	/RedSpaw P.....	Mounting bracket for 2" pipe (to C(7/16) process conn.), mat. Stainless Steel
	/RedSpaw C.....	Mounting bracket for 1" pipe (to P process conn.), mat. Stainless Steel
	/Red d/P 1/2".....	Connector to weld impulse pipes dia. 12 and 14 mm, material 15HM(SO) or SS316(S).
		Only process connection P type
Other specification	/.....	Connector to weld impulse pipes dia. 12 and 14 mm, material 15HM. Only process connection C type.
		Adapter for differential pressure transmitters with C type process connection, output thread 1/2NPT F. Material SS316L
		Description of required parameters