



## EC22 Transmitter

For monitoring toxic  
gases, H<sub>2</sub> and O<sub>2</sub>



# EC22 Transmitter

For monitoring toxic gases, H<sub>2</sub> and O<sub>2</sub>



If toxic gases, hydrogen or oxygen are to be monitored outside hazardous areas, the EC22 transmitter is a reliable and economical solution. In combination with GfG's proven controllers, the transmitter can be used in a wide variety of applications thanks to a large selection of sensors.

The EC22 operates according to the proven electrochemical measuring principle, which is characterized by a linear signal, energy efficiency and high sensitivity. It is ideal for selectively monitoring toxic gases, hydrogen or oxygen.

The EC22 hardware complies with the European Functional Safety Standard DIN EN 61508-2: 2011 for many gases. The SI levels (up to SIL3) in single-channel (1oo1) or redundant (1oo2) use are listed in the overview of gases.

## Communication and service

Signal transmission is either by 4-20 mA industry standard (alternatively 0.2-1 mA) or digitally over the RS-485 interface (Modbus / RTU). Test gas for function control and sensor adjustment can be safely supplied using a calibration adapter. All maintenance work can be carried out by a single person.



EC22 Transmitter with one cable gland for analog connection

## Reliable measurement and low operating costs

The electronics of the transmitter controls the stabilization of voltage, processing of the measured value output and detection of malfunctions at the measuring point. The built-in temperature compensation ensures highest measuring accuracy. Long-life and inexpensive sensors keep the running costs low.

## Various models for different applications

The basic version of the EC22 is sufficient for many applications. If a measured value on site is needed, there is also a version with display and acoustic alarm.

**EC22** Basic version for a wide range of electrochemical sensors

**EC22 D** With display and acoustic alarm

## Protection class and display elements

The compact housing for wall mounting is protected against splash water and dust (IP54). Two status LEDs are located on the front of the EC22 to indicate the operating status and faults as well as any service required.

In combination with GfG's powerful controllers, both versions are the ideal choice for monitoring a wide range of gases.

## Overview of gases and SI levels<sup>1</sup>:

Other gases on request.

		1oo1	1oo2
» Ammonia	(NH <sub>3</sub> )	2	3
» Chlorine	(Cl <sub>2</sub> )	1	2
» Chlorine dioxide	(ClO <sub>2</sub> )	-	-
» Hydrogen chloride	(HCl)	1	2
» Hydrogen cyanide	(HCN)	1	2

		1oo1	1oo2
» Fluorine	(F <sub>2</sub> )	1	2
» Carbon monoxide	(CO)	2	3
» Ozone	(O <sub>3</sub> )	2	3
» Oxygen	(O <sub>2</sub> )	2	3
» Sulfur dioxide	(SO <sub>2</sub> )	1	2

		1oo1	1oo2
» Hydrogen sulfide	(H <sub>2</sub> S)	1	2
» Silane	(SiH <sub>4</sub> )	-	-
» Nitrogen dioxide	(NO <sub>2</sub> )	1	2
» Nitric oxide	(NO)	1	2
» Hydrogen	(H <sub>2</sub> )	-	-

# EC22 Technical Data:

**Measuring principle:** Electrochemical (EC)  
**Measuring range:** Sensor dependent  
**Gas supply:** Diffusion or gassing per calibration adapter

**Lifetime of the sensor:** 2-3 years<sup>2</sup>

**Response time:** Sensor dependent

**Temperature:** -20 to +50 °C<sup>2</sup>  
**Humidity:** 20 to 95 % r. h.<sup>2</sup>  
**Air pressure:** 80 to 120 kPa<sup>2</sup>  
**Output signal:**  
Analog: 0.2-1 mA or 4-20 mA  
Digital: RS-485  
**Power supply:** 12 to 30 V DC  
**Housing:** Plastic

**Protection class:** IP54  
**Dimensions:** 96 x 123 x 49 mm (W x H x D)  
**Weight:** 120 to 150 g<sup>2</sup>  
**Approvals / Certifications:**  
Functional  
Safety (SIL): DIN EN 61508-2: 2011

<sup>1</sup> Depending on sensor and measuring range, <sup>2</sup> Sensor dependent

GfG Gesellschaft für Gerätebau mbH

Klönnestraße 99 | 44143 Dortmund | Germany

Phone: +49 231 56400-0 | Fax: +49 231 56400-895 | E-mail: info@gfg-mbh.com

GfGsafety.com

smart  
GasDetection  
Technologies

