



IT - Di dimensioni ridotte, la soluzione più economica per l'automazione di pompe e impianti idraulici.

EN - Reduced dimensions, the most economic solution for water pumps and plumbing systems automation.

ES - De dimensiones reducidas, es la solución más económica para la automatización de bombas e instalaciones hidráulicas.


FR - De dimensions réduites, il représente la solution la plus économique pour l'automatisation des électropompes et installations hydrauliques.

DE - Mit begrenzten Abmessungen, die wirtschaftlichste Lösung für die Automatisierung von Pumpen und Wasseranlagen.

RU - Компактное и наиболее экономичное решение для автоматизации насосов и гидравлических систем.



Contrappeso Shell - 230g¹
Shell Counterweight - 230g¹
Contrapeso Shell - 230g¹
Contrepoids Shell - 230g¹
Gegengewicht - 230g
Противовес Shell - 230 Г¹



Cavo - Cable	0,52 - 3 - 5 - 10 - 15 - 20 m	H07 RN-F 3G1 - Ø 8,8mm (1 function)
Cable - Câble		H05 RN-F 3X1 - Ø 7,5mm (2 functions)
Kabel - Кабель		H07 RN8-F 3G1 - Ø 8,8mm (1 function)
		H07 RN-F 3G1 Oil Res. - Ø 8,8mm (2 func.)

Corpo - Casing	Polipropilene - Polypropylene
Cuerpo - Corps	Polipropileno - Polypropylène
Körper - Корпус	Polypropylen - Полипропилен

Alimentazione - Power Supply	max.10(8)A 250V
Alimentación - Alimentation électrique	max.10(6)A 400V
Stromversorgung - Электропитание	

Angolo di attivazione - Activation angle	45°
Ángulo de activación - Angle d'activation	
Aktivierungswinkel - угол подключения	

Profondità - Depth	max.20m - 65,6ft
Profundidad - Profondeur	
Tiefe - Глубина	

Temperatura - Temperature	max.+50°C (+122°F)
Temperatura - Température	
Temperatur - Температура	

Grado di protezione - Protection Grade	IP 68
Grado de protección - Degré de protection	
Schutzgrad - Класс защиты	

Classe - Class	I - II
Clase - Classe	
Klasse - класс	

Certificazioni - Certification
Certificaciones - Homologations
Zulassungen - Сертификация

