

Technical specifications:

GMA200-MW16



Display & control elements

Status-LEDs:	15 status LEDs for alarms, operating and relay states
Display:	2,2" graphic display
Buttons:	5 buttons
Alarm:	buzzer max. 100dB(A) adjustable

Environmental conditions

Mounting:	only indoors up to an altitude of 2000m above sea level
for storage:	-25...+60°C 0...99%r.h. (recommended: 0...+30°C 40...60%r.h.)
for operation:	-20...+55°C 0...99%r.h.

Power supply

Operating voltage U _e :	100 V to 240 Vac 50 Hz to 60 Hz mains voltage or/and 24 Vdc (20 Vdc to 30 Vdc) through stabilized SELV or PELV power supply
Power consumption:	max. 10W (without transmitter) max. 90W (with transmitter)
Fuse:	F1=T 500 mA (for GMA200) F2=T 2.5A (for transmitter)

Transmitter connections

Supply outputs:	24 Vdc $\pm 3\%$ with built-in power supply, otherwise 20 Vdc to 30Vdc (see above) 16x 150 mA or I _{ges} =0.6 A with different allocation
Analog input signals I _{IN} :	4-20 mA or 0.2-1 mA Tolerance*: $\pm 0,3\%MR@4...20mA$ or $\pm 1,2\%MR@0,2...1mA$ (MR=measuring range) Load approx. 50...100Ω, I _{max} =70mA permanent / 500mA short time
Digital signals TRM bus1+2:	RS485; Half-Duplex; max. 38400 Baud

Measurement value processing

Update time:	1s (If there are more than 16 transmitters and relay modules on the same TRM bus and the data transmission is only at 9600 baud, the cycle time is extended from 1.0 to max. 1.3 s, so that the time of 1 s cannot be maintained)
Adjustment time for RS485:	Rise time $t_{50}<2s$ or $t_{90}<2sec$ Decay time $t_{50}<2s$ or $t_{10}<2sec$
for 4...20mA:	Rise time $t_{50}<2s$ or $t_{90}<4sec$ Decay time $t_{50}<2s$ or $t_{10}<4sec$
for 0,2...1mA:	Rise time $t_{50}<6s$ or $t_{90}<10sec$ Decay time $t_{50}<6s$ or $t_{10}<10sec$
	(extended by setting times of the gas measuring transmitters)
Ready delay:	<40s (can be extended by running-in times of gas measuring transmitters)

RS485 outputs

GMA bus:	RS485; Half-Duplex; max. 230400 Baud (for GMA200 relay modules, control centre, PC, PLC or gateway)
RS485 bus:	RS485; Half-Duplex; max. 38400 Baud (only for GMA200 relay modules)

Relay outputs

Contacts:	8 relays with normally open contact
Contact load capacity:	3A/250V AC or 3A/30V DC
Minimum switching current:	10mA
Minimum switching voltage:	5V
Switching frequency:	max. 100 per year (per relay contact), valid for SIL applications according to EN 50402
Insulation clearances:	Basic insulation between the relays: 1&2, 3&4, 5&6, 7&8 Double insulation between the relays: 2&3, 4&5, 6&7

Analogue outputs

I _{OUT} 1+2:	4-20mA with linear transfer function (load max. 560Ω)
Accuracy:	$\pm 0,3\%MR@10...30^{\circ}C$ or $\pm 0,8\%MR@-20...50^{\circ}C$ (MR=measurement/signal range)

Alarm acknowledgement inputs

Reset 1+2:	0-3V DC (alarm acknowledgement occurs on contact with GND; U _{MAX} =30V DC)
------------	--

Technical specifications:

GMA200-MW16



Data logger (optional)		max. 2 GB microSD card with FAT formatting (FAT16)	
USB connection		Mini USB socket for device configuration with PC	
Housing	Protection class:	IP65 in accordance with IEC 60529; IK08 in accordance with IEC 62262	
	Material:	Plastic	
	Dimensions:	270 x 290 x 98 mm (W x H x D)	
	Weight:	approx. 2kg	
Cable junction		Cable:	3-4 wire ≥0.75 mm² LiYY, NYM (for GMA200 supply) 2-4 wire 0.5-1.5 mm² LiYY, LiYCY (for transmitters) 2-wire 1x2x0,22mm² BUS-LD (for GMA bus with length >10 m)
	Cable glands:	max. 20 x M16x1.5 (for cable diameter 3-7 mm respectively 5-10 mm)	
	Terminal blocks:	0.08 mm2 to 2.5 mm² cross-section	
Approvals/Tests		Electromagnetic Compatibility:	EN 50270:2015 (interference emission: type class I, interference immunity: type class II)
	Electrical safety:	EN 61010-1:2010	(Pollution degree 2, overvoltage category II for mains supply) (Pollution degree 2, overvoltage category III for relay contacts)
	Functional safety:	EN 50402:2017; IEC 61508-1 to -7:2010 (SIL2/SC3) EN 50271:2018; EN 62061:2016; ISO 13849-1:2015	
	Metrological suitability:	EN 60079-29-1:2016 (EX); EN 50104:2010 (OX); EN 45544-1/-2/-3:2015 (TOX)	
Service life		20 years	

* This is only the measurement tolerance of the GMA. The transmitters have additional tolerances.